

ATLANTIS

HAZARDOUS LOCATION LED

150W & 200W HAZARDOUS LOCATION LED

- ATEX STANDARD (ZONE 1)
 - ⊕ II 2G Ex eb mb IIC T6...T4 Gb
 - ⊕ II 2D Ex tb IIIC T95°C...T125°C Db IP66
- ATEX STANDARD (ZONE 2)
 - ⊕ II 3G Ex ec mb IIC T6...T4 Gc
 - ⊕ II 2D Ex tb IIIC T80°C...T125°C Db
- IP66/67 Rated
- IK06/07 Rated (without wire guard)
- IP09 (with wire guard)
- NEMA 4X



ORDERING INFORMATION

EXAMPLE PART #: ATL - 150 - 40K - 90 - V01 - GR - BM - NDIM

SERIES	WATTS	CCT	OPTICS	INPUT PWR	FINISH	MOUNTING	DIMMING
ATL	150 200	30K 40K 50K	40 60 90 120 T3 T5	V01 110/277V	GR	PM Pole Mount TM Trunion Mount AMA Arm Mounting A AMB Arm Mounting B SF Slip Fitter Mounting BM Bracket Mounting	NDIM Non-Dimming VDIM 0-10V Dimmable

SPECIFICATIONS

- Expected Life | Over 150,000 hrs.
- Rating | IP66 & IK06 (IP67 and IK09 Opt.)
- Color Rendering Index (CRI) | >70
- Operating Temp | -40°C – +55°C
- Relative Humidity | 10-90% RH
- Power Factor | >.95
- Input Line Voltage | 100-277 VAC
- Input Line Frequency | 50/60 Hz
- Surge Protection | 4KV
- DC Output Ripple & Noise | <200mVP-P

LISTINGS

- ATEX STANDARD (ZONE 1)
 - ⊕ II 2G Ex eb mb IIC T6...T4 Gb
 - ⊕ II 2D Ex tb IIIC T95°C...T125°C Db IP66
- ATEX STANDARD (ZONE 2)
 - ⊕ II 3G Ex ec mb IIC T6...T4 Gc
 - ⊕ II 2D Ex tb IIIC T80°C...T125°C Db
- IECEX STANDARD (ZONE 1)
 - Ex eb mb IIC T6...T4 Gb
 - Ex tb IIIC T95°C...T125°C Db IP66
- IECEX STANDARD (ZONE 2)
 - Ex ec mb IIC T6...T4 Gc
 - Ex tb IIIC T80°C...T125°C Db
- Class I Zone 2 Group IIC
- Class II Zone 21 Group IIIC

MATERIALS



- Housing | Die-cast Aluminum
- Gasketing | Silicone Rubber
- Hardware | Stainless Steel
- Finish | Powdercoat
- Lens | Polycarbonate

LUMEN CHART



	3000K	4000K	5000K	
150W	19,050 lm	19,850 lm	20,250 lm	Typical delivered lumen data is approximate. Actual lumens will vary due to installation environment and beam pattern. Please see IES files.
200W	25,400 lm	26,450 lm	27,000 lm	

PRODUCT DRAWINGS (Dimensions in Inches and [mm])







150W



200W




OPTICS





Due to continuous improvement and innovation, product appearance and specifications may change without notice. Actual performance may differ as a result of end-user environment and application.



• Pole Mounting




• Slip Fitter Mounting




• Trunnion Mounting



• Bracket Mounting



• Arm Mounting (A)



• Arm Mounting (B)

