









MASTER PRODUCT COMPARISON

Updated as of 09/22/21

	INDOOR SERIES			GREENHOUSE SERIES	VEGGING SERIES			INTERLIGHTING SERIES
								
MODEL	VERTA-4	VERTA-6F	VERTA-8	LINEA 48XL	FLORA-3	FLORA-5	FLORA-10	EXTRA 60
DIMENSIONS	42" x 20" x 3.75"	48" x 42" x 3.5"	42" x 42" x 3.75"	4.2" X 48" x 4.8"	42.5" x 10.6" x 3.75"	42" x 42" x 3.75"	42" x 42" x 3.75"	42" x 42" x 3.75"
COVERAGE AREA	2' x 4'	4' x 4'	4' x 4'	Variable	1.5'x 4'	2'x 4'	4'x 4'	Variable
RECOMMENDED MOUNTING HEIGHT ABOVE CANOPY	6" ~ 12"	6" ~ 12"	6" ~ 12"	Variable	5" ~ 12"	5" ~ 12"	5" ~ 12"	Variable
PPF	822 µmol/s	1600 µmol/s	1700 µmol/s	840µmol/s	200 µmol/s	332 µmol/s	664 µmol/s	136 µmol/s
EFFICACY (±5%)	2.5 µmol/J	2.5 µmol/J	2.7 µmol/J	2.52µmol/J	2.23 µmol/J	2.23 µmol/J	2.23 µmol/J	2.23 µmol/J
SYSTEM POWER CONSUMPTION	325W	640W	640W	330W	90W	150W	300W	60W
LIFETIME	Q90>41,000hrs	Q90>41,000hrs	Q90>41,000hrs	Q90>100,000hrs	Q90>100,000hrs	Q90>100,000hrs	Q90>100,000hrs	Q90>100,000hrs
CERTIFICATIONS	ETL, CE, IP66	ETL, CE, IP66	ETL, CE, IP66	ETL, CE, IP66	ETL, CE, IP66	ETL, CE, IP66	ETL, CE, IP66	ETL, CE, IP66
DLC	Yes	In Process	Yes	Yes	Yes	Yes	Yes	Yes
LENSED	Optional	Optional	Optional	Yes	Yes	Yes	Yes	Yes
AVAILABLE SPECTRA	A1	A1	A1	A1	K1	K1	K1	M1
DIMMING CAPABILITY	0-10V (Standard) / DALI / Dim to Off / Wireless							
WARRANTY	*7-Year LED & Driver Warranty			10-Years on the Printed Circuit Board & 7-Years on Drivers				